

PowerLite™ Locator HN65J

■ MAX PowerLite 400 psi system ■

MAX developed the world's first high-pressure pneumatic nailing system and introduced it to the Japanese market in 1994. For the past decade the MAX PowerLite 400 psi system has revolutionized the construction industry in Japan. Powered by 400 psi technology, the MAX PowerLite tools are approximately 40% lighter and 20% smaller than most competitors tools without sacrificing power. Now, the MAX PowerLite system is available in the U.S. market. Experience the Next Generation in nailing technology with MAX.

FEATURES

• Compact

Compared to 100 psi joist hanger tools, the HN65J is 40% more compact.



40% smaller

• Powerful

Enough power to shoot up to 2-1/2" x .162" nails.

• Dial adjustable depth control



• New durable locator

Designed to find the hole easily and is extremely durable.



Only **4.4 lbs**

• Reduced Exhaust Air System

Side exhaust with built-in silencer.



• Trigger Lock for safety

• Maintenance free end cap filter (US Patent 5637125)



• Unique tongue free swivel fitting



- 100 nail capacity
- Easy adjustment for 1-1/2" or 2-1/2" nails

APPLICATIONS

- Strap Ties • Hurricane Ties • Joist Hangers
- Foundation Anchors and Holdowns

TOOL SPECIFICATIONS

| | |
|--------------------|------------------------------------|
| MODEL | HN65J |
| WEIGHT | 4.4 lbs |
| DIMENSIONS | 11-1/2" (H) x 4" (W) x 11-1/2" (L) |
| LOAD CAPACITY | 100 nails |
| OPERATING PRESSURE | 170 to 320 psi |




Comes with plastic carry case

FASTENERS APPLICABLE

15 degree flat plastic sheet collated nails



100 nails per coil



PowerLite Compressor AKH1050E

For the PowerLite HN65J operation, the PowerLite Compressor and PowerLite Hose are required.

PowerLite Sub tank AKTHS

• Regular pressure tools



2 p.c.

• High pressure PowerLite tools



2 p.c.



PowerLite Compressor
AKH1050E
115 V direct drive
Lightweight 51.7 lbs Compact

COMPRESSOR SPECIFICATIONS

| | |
|------------------|---|
| MODEL | AKH1050E |
| DIMENSIONS | 11-1/4" (H) x 13-5/8" (W) x 23-1/2" (L) |
| WEIGHT | 51.7 lbs. |
| POWER SUPPLY | 115 V / 60 Hz |
| RATED CURRENT | 15 A |
| PUMP | Oil-less direct drive |
| MOTOR POWER | 2 HP |
| TAKE-UP | 2.8 Gall |
| PSI | 2,300 psi |
| AIR DISPLACEMENT | 3.5 CFM @100 psi/2.0 CFM @300 psi |

Special fitting only for PowerLite Hose

The specifications and design of the products in this catalog will be subject to change without advance notice due to our continuous efforts to improve the quality of our products.

MAX

MAX USA CORP.

297 East 2nd Street Mineola, New York 11501
Phone: 800-223-4293 Fax: 516-741-3272
www.maxusacorp.com

Dealer: