

MAX

SuperFinisher®

NF255SF2/18



5 YEAR
LIMITED
WARRANTY

30 DAY
100 PSI CONSTRUCTION TOOLS
CONTRACTOR
PROMISE

18 ga. Brad Nailer

MAX

SuperFinisher®

NF255SF2/18

TOOL FEATURES

1 PATENTED AIR DUSTER (Patent No. US8393511B2, US7950557B2)

Push this button to disburse air to quickly clear dust and debris from the work surface.

2 PRECISION POINT CONTACT NOSE

Easily fasten trim in narrow spaces. The precision nose guides nails to an exact area on the work surface. Provides consistent performance while toe nailing.

3 FLAT-TOP BODY

The tool's flat top design allows nails to be fired as close as 1/8" from a vertical wall/surface.

4 NO MAR CONTACT TIP

Eliminates driver marks to deliver a beautiful finish on wood trim.

5 ENHANCED DRIVING POWER

Powerful enough to shoot brad nails into hard materials.

6 DEPTH ADJUSTMENT DIAL

Effortlessly drive nails into hard materials, but also control depth of drive when fastening soft materials, for a consistently polished finish.

7 BUILT-IN SURFACE PROTECTION SHIELDS

A Thermoplastic Elastomer Cylinder Cap and strategically placed plastic components, prevent the tool's metal parts from touching worksurfaces. This feature hinders the tool from damaging finished worksurfaces.

8 ANTI-DRY FIRING MECHANISM

This mechanism prohibits the tool from firing when 7 nails remain in the magazine. This feature prevents surface damage that can occur during dry-fires.



TOOL SPECIFICATIONS

Weight	2.9 lbs
H x W x L	9-3/8" x 2-5/8" x 10-1/4"
Loading Capacity	100 brad nails
Operating Pressure	60 to 100 psi
Air Consumption	0.02 ft ³ /cycle at 100 psi

FASTENER SPECIFICATIONS

Nail Length	5/8" to 2- 1/8"
Shank Diameter	0.41"
Gauge	18 ga.
Head Diameter	.075"/.051"
Collation Angle	Straight

APPLICATIONS ▶▶

Finish & Trim | Door/Window Casing | Cabinets | Panel Assembly
Subflooring

MAX

MAX USA CORP.

205 Express St, Plainview NY 11803

800-223-4293

www.maxusacorp.com

DEALER: